

Optically Thin Metallic Films for High-Radiative-Efficiency Plasmonics

Yi Yang,*^{,†} Bo Zhen,^{†,‡} Chia Wei Hsu,[¶] Owen D. Miller,[§] John D. Joannopoulos,[†] and Marin Soljačić[†]

[†]Research Laboratory of Electronics, Massachusetts Institute of Technology, Cambridge, Massachusetts 02139, United States [‡]Physics Department and Solid State Institute, Technion, Haifa 320000, Israel

^{II}Department of Applied Physics, Yale University, New Haven, Connecticut 06520, United States

[§]Department of Mathematics, Massachusetts Institute of Technology, Cambridge, Massachusetts 02139, United States

(5) Supporting Information

ABSTRACT: Plasmonics enables deep-subwavelength concentration of light and has become important for fundamental studies as well as real-life applications. Two major existing platforms of plasmonics are metallic nanoparticles and metallic films. Metallic nanoparticles allow efficient coupling to far field radiation, yet their synthesis typically leads to poor material quality. Metallic films offer substantially higher quality materials, but their coupling to radiation is typically jeopardized due to the large momentum mismatch with free space. Here, we propose and theoretically investigate optically thin metallic



films as an ideal platform for high-radiative-efficiency plasmonics. For far-field scattering, adding a thin high-quality metallic substrate enables a higher quality factor while maintaining the localization and tunability that the nanoparticle provides. For near-field spontaneous emission, a thin metallic substrate, of high quality or not, greatly improves the field overlap between the emitter environment and propagating surface plasmons, enabling high-Purcell (total enhancement $>10^4$), high-quantum-yield (>50%) spontaneous emission, even as the gap size vanishes (3–5 nm). The enhancement has almost spatially independent efficiency and does not suffer from quenching effects that commonly exist in previous structures.

KEYWORDS: nanoparticles, optical nanoantennas, radiative efficiency, metallic thin film, light scattering, spontaneous emission

hmic loss in metals is the most critical restriction for plasmonics.¹ The restriction can be characterized by the radiative efficiency η , defined as the ratio between the radiative decay rate and the total decay rate, that is, $\eta = \gamma_{rad}/\gamma_{tot}$. Two major existing platforms of plasmonics are metallic nano-particles²⁻⁷ and metallic films;⁸⁻¹¹ they both face their own restrictions for achieving a high η . A major problem regarding nanoparticles is their poor material qualities due to the amorphous structures that arise from the colloidal synthesis processes. In comparison, single- or polycrystalline metallic films fabricated via temperature-controlled sputtering or epitaxial growth can achieve much higher material qualities and much lower material losses, but their coupling to radiation is typically jeopardized due to the large momentum mismatch with free space. When the two platforms are combined, the radiation of nanoparticles is also at risk of being quenched by a bulk nearby metallic film. These restrictions lead to compromises between η and other mode properties, such as quality factor (Q) and mode volume $^{12-14}$ (V).

For plasmonic light scattering, it is often desirable to achieve high radiative efficiencies and high Q simultaneously. In biomedical sensing,¹⁵⁻¹⁸ for example, a high Q is required for high spectral resolution, whereas a high radiative efficiency (stronger scattering) is needed for high signal-to-noise ratio (SNR). Meanwhile, transparent displays¹⁹⁻²¹ based on resonant scattering demand high Q for high transparency and high radiative efficiencies for high brightness. However, it is very challenging to achieve both goals at the same time. First, Q, σ_{exv} and σ_{sca} are all bounded from above as functions of the permittivities of materials,^{22–25} primarily due to the intrinsic material loss. Second, there exists a fundamental physical contradiction between the two requirements: higher radiative efficiencies require higher radiative decay rates, which necessarily reduce the total quality factors.

For plasmon-enhanced emission,^{26–32} another trade-off exists between achieving high quantum yield (QY) and large Purcell³³ factors, even though both are typically desired. The key to achieving high spontaneous emission enhancement over a broad band^{32,34} using plasmonics is to achieve small Vs. However, as V decreases, absorptive decay rates (proportional to V^{35}) dominate over radiative decay rates (proportional to V^{235}), triggering a drastic drop in QY.^{31,36,37} Recently, much effort has been made to enhance spontaneous emission using gap plasmons,^{28–30,36,38–40} created via the confinement of light within the dielectric gap between nanoparticles and an optically thick metallic substrate. Compared with other types of resonances, the gap plasmon resonance achieves high total enhancement³⁰ as it offers more reliable control of the dielectric

Received:February 26, 2016Revised:May 26, 2016Published:May 31, 2016



Figure 1. (a) Structure: a torus sitting on top of a metallic multifilm. The major and minor (cross section) radii are denoted by R = 36 nm and r = 14 nm, respectively. The thicknesses of the upper and lower amorphous TiO₂ layers are fixed at 5 and 20 nm, respectively. The thickness of the middle epitaxial silver layer is denoted by t. (b) E_z profiles of two eigenmodes when t = 3.4 nm in x-z (left) and x-y (right) planes. Upper: gap plasmon resonance. Lower: torus (Mie) plasmon resonance. Scattering and extinction cross sections of the torus on a (c) thick metal film (t = 30 nm) and (d) thin metal film (t = 3.4 nm), respectively. The radiative efficiency η increases significantly when metal thickness is reduced.

gap thinness. However, these gap plasmon resonances cannot circumvent the trade-off between QY and V. For example, when the gap size is reduced to 5 nm or smaller for a nanocube, despite a higher total decay rate, the efficiency (defined as the sum of photon and plasmon radiative efficiency^{29,30,36}) drops below ~20%.^{30,36} Moreover, the efficiency is strongly dependent on the location of emitters. QY reaches maximum if the emitter is placed at the center of the gap but decreases immensely when the emitter is in the proximity of the metal.³⁰

Here, we propose and theoretically demonstrate that an optically thin metallic film makes an ideal platform for highradiative-efficiency plasmonics via two examples: high-Q scattering and enhanced emission. For scattering, a high-quality thin metallic film facilitates a high-Q, high-radiative-efficiency Mie plasmon resonance, whose Q exceeds the quasistatic Q of the nanoparticle material. For enhanced emission, gap plasmons can still be well supported and are better mode overlapped with external radiation using an optically thin metallic substrate. A high-Purcell (total enhancement $>10^4$), spatially independent-efficiency (>50%) spontaneous emission enhancement can be achieved with vanishing gap size (3-5)nm), even if the substrate has the same material properties as the nanoparticles. Our platform can also be extended to other applications (for example, nonlinear frequency generation and multiplexing), because of the enhanced efficiencies of highorder plasmonic modes. Moreover, the ratio between photon and plasmon radiation can be easily tailored by altering the shape of the nanoparticles, making this platform versatile for both fluorescence²⁹⁻³¹ and plasmon circuits.⁴¹⁻⁴⁴

Below, we show that in plasmonic optical scattering, the quasistatic Q of a deep subwavelength nanoparticles can be exceeded with the help of an optically thin high-quality metal film while maintaining considerably high radiative efficiencies η , which is also known as the scattering quantum yield¹⁵ or the

albedo⁴⁵ in scattering problems. For a subwavelength scattering process, based on temporal coupled-mode theory,^{46,47} the radiative efficiency η and the total quality factor Q_{tot} for a single resonance are given by

$$\eta \equiv \frac{\gamma_{\rm rad}}{\gamma_{\rm tot}} = \frac{\sigma_{\rm sca}}{\sigma_{\rm ext}} \bigg|_{\rm on\,resonance} \tag{1}$$

$$Q_{tot} = \frac{\omega_0}{2\gamma_{tot}}$$
(2)

where ω_0 is the resonant frequency, $\gamma_{tot} = \gamma_{rad} + \gamma_{abs}$ is the total decay rate, and $\sigma_{ext} = \sigma_{sca} + \sigma_{abs}$ is the extinction cross-section. As γ_{abs} is mostly dictated by material absorption,^{22,23} to get a high η , one has to increase γ_{rad} . This in turn spoils the quality factor (eq 2), which reveals the trade-off between η and Q_{tov} as we described previously. Because simultaneously achieving a high Q and a high η is important for many applications, like biomedical sensing^{15–18} and transparent displays,^{19–21} we define the figure of merit (FOM) for scattering as

$$FOM_{sca} = \frac{Q_{tot}}{1 - \eta}$$
(3)

It follows that this FOM reduces to the quasistatic quality factor Q_{qs}^{22}

$$FOM_{sca} = \frac{\omega_0}{2\gamma_{abs}} = Q_{abs} \simeq Q_{qs} = \frac{\omega \frac{d\epsilon}{d\omega}}{2\epsilon''}$$
(4)

which only depends on the material property of the nanoparticle. Here, ϵ' and ϵ'' are real and imaginary parts of the complex permittivity. For subwavelength metallic nanoparticles (dimension $\ll \lambda$), their plasmon properties are typically dominated by quasistatic considerations,²² and thus,

the approximation $Q_{\rm abs} \simeq Q_{\rm qs}$ holds, which also indicates that the material loss inside the metallic nanoparticle cannot be further reduced. Therefore, our strategy is to squeeze parts of the resonant mode into a high-quality metallic film^{8,9} with much lower loss while maintaining efficient radiation rates.

As an example, we investigate a silver torus⁴⁸⁻⁵¹ scatterer. sitting on top of a TiO₂-Ag-TiO₂ multifilm, whose structural geometry is shown in Figure 1a. The permittivities of the silver film and the torus are obtained from Wu⁸ and Palik,⁵² respectively; the former has substantially lower loss because it is assumed to be made epitaxially. The permittivity of amorphous TiO_2 (refractive index ~2.5 in the visible and near-infrared spectra) is from Kim.⁵³ The material absorption in TiO_2 is negligible compared with the absorption in silver, as $Im(\epsilon_{TiO_2})$ is several orders of magnitude lower than that of $Im(\epsilon_{Ag})$ within the wavelength range of interest. Thus, the absorption in TiO₂ is not considered in the calculation. The ambient index of refraction is 1.38 (near the refractive index of water, tissue fluids, and various polymers). If the structure is probed with normally incident plane waves, only the m = 1 (*m* is the azimuthal index of the modes because the structure is axially symmetric) modes of the structure can be excited.³⁵ Figure 1b shows the mode profiles of the two m = 1 resonances in this structure. Resonance A is a gap plasmon resonance³⁹ whose field is mostly confined in the upper TiO₂ layer. Resonance B corresponds to the torus (Mie) plasmon resonance,⁵⁴ given that it maintains a nodal line (green dashed line in Figure 1b) along z = r (r is the minor radius of the torus), which is a feature of the torus resonance in free space.⁴⁸⁻⁵¹ Figure 1c and d compare σ_{sca} and σ_{ext} of the torus when the silver layer in the multifilm is optically thick (t = 30 nm) or thin (t = 3.4 nm). For both resonances, the radiative efficiency in the thin-film case is much higher than that in the thick-film case. Moreover, when the torus moves away from the multifilm, the response of resonances is very different for the thin film case from that for the thick film, as shown in Figure S1. We now focus on the Mie resonance B for high-Q scattering as most of its entire radiation (photon and plasmon combined) goes into the far field (photon). We will return to the gap plasmon resonance A later for enhanced emission applications.

By changing t from 0 to 50 nm while keeping other parameters unchanged (t = 0 nm corresponds to a single 25 nm TiO_2 layer), we are able to track the torus plasmon resonance B and evaluate its FOM_{sca} , as shown in Figure 2. As t increases, the resonance blue-shifts, along with a reduced line width (Figure 2a). In Figure 2b, we compare the FOM_{sca} in our structure to the quasistatic limit Q_{as} for different materials in the system: the Palik silver⁵² that is used for the torus and the epitaxial silver that is used for the substrate⁸ (FOM_{sca} and Q_{as} are directly comparable; see eqs 3 and 4). There exists a plateau of higher FOM_{sca} at t = 3-10 nm. At these thicknesses, the multifilm still has very high transmission >80% (Figure S2). The FOM_{sca} of the torus plasmon resonance exceeds and becomes twice as high as the $Q_{\alpha s}$ of the torus material (Palik⁵²). When the silver layer is either too thin (<3 nm) or too thick (>20 nm), the FOM_{\rm sca} drops considerably and FOM_{\rm sca} \lesssim $Q_{\rm ns}$ (Palik), the quasistatic quality factor of the torus material. Figure 2c shows that the high FOM_{sca} can be maintained for both polarizations over a wide range of incident angles.

The increased quality factor is the result of effective mode squeezing that only occurs in thin silver films, an effect we qualitatively demonstrate in Figure S3 of the Supporting



(a)

Ag film thickness [nm]

(b)

(c)

Torus

Multi

Figure 2. (a) Scattering cross section $\sigma_{\rm sca}$ of torus plasmon resonance decreases as the silver film thickness t increases. (b) $FOM_{sca} = Q_{tot}/$ $(1-\eta) \simeq Q_{\rm qs}$ shows that our structure can exceed the quasistatic limits for the Palik silver used in the nanoparticle. When the silver film is optically thin (t = 3-10 nm), a plateau of FOM_{sca} ~ 40 exceeding quasistatic limit of the Palik silver is achieved for resonant wavelengths at 600-800 nm, as denoted by the dashed green lines. The blue dots are calculated via eq 3 from the time-domain scattering simulation. The blue line is calculated via eq 7 from the frequency-domain eigenmode simulation. (c) Angular dependence of the scattering cross section of the torus plasmon resonance with t = 3.4 nm under the excitation of TE and TM polarizations.

0

700

750

Wavelength [nm]

800

850

Information. The mode squeezing mechanism can be quantitatively demonstrated by calculating the energy density integral of the eigenmode. The energy density u in lossy media is generally defined as $u = \epsilon_0 (\epsilon' + (2\omega \epsilon''/\gamma)) |E|^2/2,^{55}$ where ϵ' and ϵ'' are real and imaginary parts of permittivity respectively, and γ is the damping of the metal. We adopt $\gamma = 1.4 \times 10^{14} \text{ rad}/$ s for the Palik silver and $\gamma = 3.14 \times 10^{13}$ rad/s for the epitaxial silver to best match the tabulated data. Because the metallic objects (Palik silver torus and epitaxial silver film) dominate the absorption loss in this system, we define the energy concentration coefficients in the torus and the film as

$$c_{\text{torus}} = \frac{\int_{\text{torus}} u dV}{\int_{\text{torus}} u dV + \int_{\text{film}} u dV}$$
(5)

8



Figure 3. Mode-overlap analysis showing the advantage of using optically thin substrates for gap plasmon emission enhancement. Improved mode matching of surface plasmon polaritons (SPPs) comparing (a) the metal–insulator–metal and insulator–metal (MIM-IM) interface with a 12% overlap to (b) the metal–insulator–metal–insulator and insulator–metal–insulator (MIMI-IMI) interface with a 41% overlap. (a), (b) Case of a metallic particle interacting with an optically thick and thin metallic film, respectively. Black solid curves show $|E_z|$ mode profiles of different SPPs. For these calculations, we used Palik⁵² silver for the metallic layers, refractive index of 1.4 for the insulator layers, dielectric gap sizes of 5 nm, and the thickness of the metallic substrate as semi-infinite for (a) and 10 nm for (b). (c) Dispersion relations of SPPs. (d) Mode overlap dispersion in the MIM-IM and MIMI-IMI interfaces.

$$c_{\rm film} = \frac{\int_{\rm film} u dV}{\int_{\rm torus} u dV + \int_{\rm film} u dV}$$
(6)

Thus, the Q_{qs} of the system can be estimated as

$$\frac{1}{Q_{qs}} = \frac{c_{torus}}{Q_{qs}(Palik)} + \frac{c_{film}}{Q_{qs}(Epitaxy)}$$
(7)

As shown in Figure 2b, the Q_{qs} of the system, calculated from the scattering (blue dots) and eigenmode (blue curve) simulations respectively, match each other well. Our calculation shows the high energy concentration in the film only happens when the film is optically thin (see Figure S4). Near the maximum of the Q_{qs} (wavelength ~700 nm, silver film thickness ~7 nm), the energy concentrated in the film is three times higher than that in the torus ($c_{film} ~ 3c_{torus}$). We also note that the Q_{qs} curves of the two materials are quite flat within the wavelength of interest. Thus, it is the effective mode squeezing into a high-quality film, rather than the dispersion of an individual material, that contributes to the improved quality factor of the system.

The aforementioned enhanced Q is different from the line width narrowing that is based on the interference between multiple resonances.² For coupled resonances, as the trace of the full Hamiltonian is conserved, the line width reduction of one resonance necessarily implies the broadening of the others'. This coupling also typically renders the spectrum Fano-like with dark states in the middle of the spectrum.⁵⁶ In contrast, here the line width reduction is realized via effectively squeezing a single Mie plasmon mode into an optically thin metallic film. Scattering spectrum is kept single-Lorentzian, which is favorable for many applications,^{16–19,21} as it maintains a high resolution and SNR. Moreover, as the resonance for scattering uses the Mie plasmon and the ambient environment

is the perturbed free space, most of the reradiated energy goes into the far field with weak plasmon excitation (see Supporting Information). We also note that optically thin metallic films are not restricted to high-Q applications shown above. Applications based on broadband strong scattering (like solar cells requiring longer optical path) can also be implemented on this platform, utilizing its high radiative efficiency.

Antennas work equally well as receivers and as transmitters; in the context of nanoparticles, the radiative efficiency η is equally important, whether nanoparticles are used to scatter light from the far field or serve as external cavities to enhance spontaneous emission in the near field. The quantum yield (QY) of an emitter (whose total decay rate is Γ_0 in free space) enhanced by a plasmonic nanoparticle can be approximated as³² QY $\simeq \eta \Gamma_g / \Gamma_{tot}$ under the assumption that the decay rate is dominated by the plasmonic resonance (note that we use Γ and γ to denote the emission and scattering processes, respectively). Here, $\Gamma_{tot} = \Gamma_g + \Gamma'_0 + \Gamma_{nr}^{em} + \Gamma_q$, Γ'_0 is the radiative decay rate of the emitter not coupled to the cavity, $\Gamma_{\rm g}\simeq\Gamma_{\rm rad}+\Gamma_{\rm abs}$ is the modified emission rate in the presence of the cavity, Γ_{rad} and Γ_{abs} are radiative and absorptive decay rates of the cavity, respectively, Γ_{nr}^{em} is the intrinsic nonradiative decay rate of the emitter, and $\Gamma_{\rm q}$ is the quenching rate that refers to the loss induced by the direct heating of the metal from the emitter without coupling to optical resonances. In most cases, Γ_g is dominant over all other components of Γ_{tot} and Γ_{rad} is much larger than Γ'_0 ; therefore, we can further approximate QY as the radiative efficiency of the nanoparticle, that is, QY $\simeq \eta$. For enhanced emission, it is often desired to simultaneously achieve high quantum yield and high decay rates, so we define the FOM for enhanced emission as

$$FOM_{emit} = \eta \cdot F_p \propto \frac{\eta}{V}$$
(8)





Figure 4. (a) Structure for spontaneous emission enhancement: a silver cylinder (diameter and height both 50 nm) sitting on top of a silver substrate (thickness *t*) and a dielectric (SiO₂, n = 1.4) gap (thickness *g*). Free space refractive index is 1.4. (b) Normalized electric field $|E|/|E_0|$ of the gap plasmon resonance with t = 10 nm and g = 5 nm. Electric field is mostly confined within the dielectric gap. The white arrow denotes a *z*-polarized dipole emitter and the red solid box defines the sweeping area of the dipole location. Orange dashed lines outline the interfaces between different layers. (c) Radiative enhancement and (d) radiative efficiency in the x-z plane as a function of dipole location (left, t = 10 nm; right, t = 50 nm) with fixed g = 5 nm. (e) Evolution of radiative enhancement (upper) and efficiency (lower) as a function of dielectric gap size *g*, with a thin (t = 10 nm) and thick (t = 50 nm) silver substrate. The green arrow indicates the increase of efficiency by decreasing substrate thickness. The size of the cylinder changes accordingly with different *g* to maintain the resonance at ~700 nm. The dipole stays at the center of the gap, and under the edge of the cylinder.

where $F_{\rm p} = \Gamma_{\rm tot}/\Gamma_0$ is the Purcell factor³³ and *V* is the mode volume.^{12–14} Note that *Q* does not show explicitly in eq 8 as the broadband plasmonic enhancement relies on *V* much more than on *Q*. It follows that FOM_{emit} reduces to the radiative enhancement $\Gamma_{\rm rad}/\Gamma_0$.

Recently, gap plasmons^{28–30,36,38–40} show their advantage in spontaneous emission enhancement for the corresponding more reliable control of the dielectric gap thinness. An optically thick metallic substrate is commonly used in previous reports,^{28–30,36,40,57,58} in order to obtain the highly confined metal–insulator–metal (MIM) SPP within the dielectric gap. However, the thick film also induces large mode absorption, when the dielectric gap vanishes. Moreover, the QY of an emitter inside the gap is especially sensitive to its vertical position; the maximum QY is usually achieved if the emitter is placed at the center of the gap but becomes extremely low if the emitter is placed near metal.

To begin with, we show why optically thin metallic substrates can facilitate high-Purcell and high radiative-efficiency plasmonics via a mode-overlap analysis. Film-coupled nanoparticles can be understood as Fabry–Perot cavities^{59–61} of gap plasmons, with two radiative channels: one into propagating surface plasmon polaritons (SPPs), and another into photons via adiabatic tapering effect^{54,62,63} using nanoparticle edges. Figure 3a shows the conventionally used metal–insulator– metal (MIM) SPP for emission enhancement. If we reduce the thickness of metal substrate so that it is smaller than the skin depth of MIM SPP, the lower dielectric half space starts to have a decaying tail. We call this new type of SPP the metal– insulator-metal-insulator (MIMI) SPP (Figure 3b). Surprisingly, although we use less metal, the MIMI SPP achieves better light confinement (smaller $\partial \omega / \partial k$) than the MIM SPP given the same frequency, as shown in the dispersion diagram (Figure 3c). This indicates that the on-resonance local density of states of the MIMI SPP will be higher than that of the MIM SPP, if one replaces the top metal layer with a nanoparticle as a frequency-selecting cavity. A better mode overlap^{62,64} (middle of Figure 3a,b and see Supporting Information) between the gap plasmon with the corresponding propagating SPP implies a larger radiative decay rate into propagating SPP than that in the case using an optically thick film. Figure 3d shows that the MIMI-IMI overlap is much larger than the MIM-IM overlap over a wide wavelength range, from near-infrared to the entire visible spectrum. Note that although the above analysis only discusses the mode matching between gap and propagating SPPs, the photon decay rate can be greatly enhanced via tapering the SPPs into photons using the momenta provided by nanoparticle edges, which we will show later.

Next, we move from the analytical modal analysis to rigorous computations of the enhanced emission characteristics for realistic structures. We consider a structure with a silver cylinder on top of a silver thin film (Figure 4a). The permittivities of the cylinder and the film are both Palik silver⁵² to offer a worst-case scenario analysis. For this structure, the radiative (photon + plasmon) efficiency η is calculated to be $\eta \sim 60\%$ and $\eta \sim 30\%$ for t = 10 and t = 50 nm respectively using the scattering and extinction cross sections of the cylinder, as shown in Figure S5. As the electric field is

dominated by E_z , a z-polarized dipole (marked by the white arrow) is placed within the gap to probe the enhancement (Figure 4b). A sweeping analysis of dipole location in the x-zplane (marked by the solid red box) provides all the information about the enhancement due to the rotational symmetry of the structure. As shown in Figure 4c, the radiative decay rate $\Gamma_{\rm rad}/\Gamma_0$ is generally higher with the thin film (t = 10nm) than that with the thick film (t = 50 nm). More surprisingly, η in the t = 10 nm case remains almost uniformly high in the x-z plane with an average of ~60%, while that in the t = 50 case drops to ~30% (Figure 4d. Both results are consistent with their scattering-extinction ratio (Figure S5). Note that in the t = 10 nm case, Γ_{rad}/Γ_0 remains high even for dipole locations within 1 nm distance from the metal surface, where absorption is always considered dominant.^{26,30,31} If epitaxial silver is used for the metal substrate, similar results are obtained with even higher η_i as shown in Figure S6. Figure 4e compares $\Gamma_{\rm rad}/\Gamma_0$ and η as a function of dielectric gap size for t = 10 and t = 50 nm cases, with a fixed emitter at the center of the gap, and under the edge of the cylinder. The trends of $\Gamma_{\rm rad}$ Γ_0 are similar. For η , in the t = 10 nm case it remains higher for all gap sizes. The advantage becomes more striking with vanishing gap size (3-8 nm), where the thin substrate achieves a much higher enhancement and efficiency simultaneously.

The optically thin metallic susbstrates have two main advantages compared to the thick ones. First, the cavity mode becomes less absorptive as shown by the loss per volume (smaller Γ_{abs} , see Figure S5). Second, the radiative decay rate is enhanced (larger Γ_{rad}) because of the improved mode overlap condition (Figure 3).

As there are two radiative channels in the gap plasmon structure (i.e., free space radiation into the far field Γ_{far} and SPP excitation Γ_{SPP}), it is important to separate the total radiative decay rate Γ_{rad} into the two channels (see Supporting Information) and know how to tailor their relative ratio. It has been shown that tapered antennas (particles like spheres and tori) have higher radiative efficiencies than rigid antennas (particles like cubes and cylinders).³⁶ Here, we show the ratio of Γ_{far} and Γ_{SPP} in the entire radiation can be tailored via the shape of nanoparticles. We replace the cylinder with a torus, as shown in Figure 5. There are multiple orders of gap plasmon resonances (whispering gallery modes with the dielectric gap) in this structure. Usually the decay of high-order resonances of a plasmonic nanoantenna is dominated by absorption and thus are not very efficient for excitation or radiation. However, with a thin metal substrate, the first three gap plasmon resonances of the structure (denoted by their azimuthal index m) all achieve considerably high enhancement while maintaining high efficiencies (Figure 5a). This result reveals the potential for high-efficiency harmonic generation and wave multiplexing. For the cylinder, Γ_{SPP} is the dominant radiative channel (Figure 5b, left), making this structure an ideal candidate for a high excitation-efficiency plasmon source.^{41–44} Although for the torus, Γ_{far} is greatly boosted, which is useful for fluorescence applications^{29–31} (Figure 5b, right). Note that although the photon and plasmon excitation ratio is different in the two nanoparticles, it is the thin metallic substrate that gives rise to the high total radiative enhancement.

The aforementioned high-Q scattering and high-QY emission are deeply connected via the radiative efficiency η but differ from each other. For scattering, $\text{FOM}_{\text{sca}} = Q/(1 - \eta)$. For plasmon-enhanced emission, $\text{FOM}_{\text{emit}} \propto \eta/V$. Thus, two applications focus on Q and V, respectively. What they need in



Figure 5. (a) Optically thin metal films enable high radiative efficiencies even for high-order (large-azimuthal-index, m) modes, which are typically less efficient in plasmonics. Emission enhancement and radiative efficiency of the torus-multifilm structure (R = 28 nm, r =24 nm, and t = 5 nm. Other configurations are the same as those defined in Figure 1) are shown. Upper inset: E_z profiles in the middle of the dielectric gap of the m = 1, 2, 3 gap plasmon modes. Lower inset: Normalized electric field of the gap plasmon resonance of the torus with illustrated major decaying channels; free space radiation into the far field Γ_{far} , launched SPP Γ_{SPP} , and absorption Γ_{abs} (including quenching and mode absorption). The white two-sided arrow indicates the location of the z-polarized dipole. Green dash lines denote the interfaces of different layers. (b) Radiation into surface plasmons can be converted to radiation in the far field by altering the nanoparticle shape, for example, from a cylinder to a torus. The key to the large total ($\Gamma_{far} + \Gamma_{SPP}$) radiative emission, in either case, is the use of a thin-film metallic substrate.

common is a higher η for either stronger scattering or higher quantum yield. Another difference is that a high-quality metallic substrate is not essential for high-efficiency (>50%) emission (compare Figure 4c,d with Figure S6), as the improved mode matching does not rely on low-absoprtion materials. Nevertheless, it is necessary if one intends to exceed the Q_{qs} of the nanoparticle material by using the thin metallic substrate (see Figure 2).

It is also important to consider the practical feasibility of fabricating such high-quality thin films, and whether the material can be approximated with a local (bulk) permittivity. Theoretically, nonlocal effects⁶⁵ induce additional loss when the dimension of plasmonic structures becomes small. Specifically for multifilms, the nonlocal effects are typically insignificant with geometrical sizes larger than $1-2 \text{ nm}^{66}$ (or > $\lambda_p/100$,⁶⁷ λ_p is the plasma wavelength) in the gap plasmon resonances. In addition, the nanoparticles discussed in this Letter are generally large enough (size >20 nm) such that the nonlocal effects are negligible, yet small enough (size < $\lambda/10$) such that the

quasistatic approximation still holds. Overall, the local response approximation is still valid in the above analysis. Practically, the low-temperature epitaxial growth technique can provide a low growth rate (typically 1 Å/min⁸) while maintaining high film quality, making this technique ideal for the fabrication of low-loss ultrathin film (≤ 10 nm).

In this Letter, we show that optically thin metallic films offer an ideal platform for high-radiative-efficiency plasmonics. Using a thin metallic substrate, we achieve high-Q and strong scattering that exceeds the quasistatic limit of the nanoparticle material. On the basis of the improved mode matching condition, we predicted large Purcell ($F_p > 10^4$) and high efficiency (>50%) for gap-plasmon-enhanced spontaneous emission, maintained over the whole active region. Future efforts can be made on particle designs that enable accurate and high dynamic-range control of the plasmon and photon excitation. It will also be interesting to study how resonances interfere^{56,68,69} with each other on this platform.

ASSOCIATED CONTENT

S Supporting Information

The Supporting Information is available free of charge on the ACS Publications website at DOI: 10.1021/acs.nano-lett.6b00853.

Numerical methods (Supplementary Texts); Analytical mode overlap calculation (Supplementary Texts); Evolution of Mie and gap plasmon resonances when the torus is moving toward the multifilm (Figure S1); Multifilm transmission (Figure S2); Mode squeezing (Figure S3); Energy concentration coefficients as functions of the silver film thickness (Figure S4); Radiation efficiencies of the silver cylinder and corresponding absorption per volume for thin and thick silver substrates (Figure S5); Spontaneous emission enhancement using epitaxial-grown silver substrates (Figure S6). (PDF)

AUTHOR INFORMATION

Corresponding Author

*E-mail: yiy@mit.edu.

Notes

The authors declare no competing financial interest.

ACKNOWLEDGMENTS

The authors thank Prof. Koppens for the suggestion to look into epitaxially grown silver. The authors thank Di Zhu, Adi Pick, Dr. Homer Reid, and Dr. Jianji Yang for helpful discussions. Y.Y. was partly supported by the MRSEC Program of the National Science Foundation under Grant No. DMR-1419807. B.Z. and M.S. were partly supported by S3TEC, an Energy Frontier Research Center funded by the U.S. Department of Energy under grant no. DE-SC0001299. B.Z. was partially supported by the United States–Israel Binational Science Foundation (BSF) under award no. 2013508. C.W.H. was partly supported by the National Science Foundation through grant no. DMR-1307632. O.D.M. was supported by the Army Research Office through the Institute for Soldier Nanotechnologies under contract no. W911NF-13-D-0001.

REFERENCES

- (2) Sobhani, A.; Manjavacas, A.; Cao, Y.; McClain, M. J.; García de Abajo, F. J.; Nordlander, P.; Halas, N. J. *Nano Lett.* **2015**, *15*, 6946–6951.
- (3) Liu, W.; Miroshnichenko, A. E.; Neshev, D. N.; Kivshar, Y. S. ACS Nano 2012, 6, 5489–5497.
- (4) Chang, W.-S.; Willingham, B. A.; Slaughter, L. S.; Khanal, B. P.; Vigderman, L.; Zubarev, E. R.; Link, S. *Proc. Natl. Acad. Sci. U. S. A.* **2011**, *108*, 19879–19884.

(5) Peer, D.; Karp, J. M.; Hong, S.; Farokhzad, O. C.; Margalit, R.; Langer, R. Nat. Nanotechnol. 2007, 2, 751-760.

(6) Ota, S.; Wang, S.; Wang, Y.; Yin, X.; Zhang, X. Nano Lett. 2013, 13, 2766–2770.

(7) Maier, S. A.; Kik, P. G.; Atwater, H. A.; Meltzer, S.; Harel, E.; Koel, B. E.; Requicha, A. A. *Nat. Mater.* **2003**, *2*, 229–232.

(8) Wu, Y.; Zhang, C.; Estakhri, N. M.; Zhao, Y.; Kim, J.; Zhang, M.; Liu, X.-X.; Pribil, G. K.; Alù, A.; Shih, C.-K.; Li, X. *Adv. Mater.* **2014**, 26, 6106–6110.

(9) McPeak, K. M.; Jayanti, S. V.; Kress, S. J.; Meyer, S.; Iotti, S.; Rossinelli, A.; Norris, D. J. ACS Photonics **2015**, *2*, 326–333.

(10) Babar, S.; Weaver, J. Appl. Opt. 2015, 54, 477-481.

- (11) Miller, O. D.; Johnson, S. G.; Rodriguez, A. W. Phys. Rev. Lett. 2014, 112, 157402.
- (12) Koenderink, A. F. Opt. Lett. 2010, 35, 4208-4210.
- (13) Sauvan, C.; Hugonin, J.-P.; Maksymov, I.; Lalanne, P. Phys. Rev. Lett. 2013, 110, 237401.
- (14) Kristensen, P. T.; Hughes, S. ACS Photonics **2014**, 1, 2–10.
- (15) Lee, K.-S.; El-Sayed, M. A. J. Phys. Chem. B 2005, 109, 20331– 20338.

(16) El-Sayed, I. H.; Huang, X.; El-Sayed, M. A. Nano Lett. 2005, 5, 829-834.

(17) Anker, J. N.; Hall, W. P.; Lyandres, O.; Shah, N. C.; Zhao, J.; Van Duyne, R. P. *Nat. Mater.* **2008**, *7*, 442–453.

(18) Saha, K.; Agasti, S. S.; Kim, C.; Li, X.; Rotello, V. M. Chem. Rev. **2012**, *112*, 2739–2779.

(19) Hsu, C. W.; Zhen, B.; Qiu, W.; Shapira, O.; DeLacy, B. G.; Joannopoulos, J. D.; Soljačić, M. Nat. Commun. 2014, 5, 3152.

(20) Hsu, C. W.; Miller, O. D.; Johnson, S. G.; Soljačić, M. Opt. Express 2015, 23, 9516-9526.

- (21) Saito, K.; Tatsuma, T. Nanoscale 2015, 7, 20365-20368.
- (22) Wang, F.; Shen, Y. R. Phys. Rev. Lett. 2006, 97, 206806.
- (23) Raman, A.; Shin, W.; Fan, S. Phys. Rev. Lett. 2013, 110, 183901.

(24) Miller, O. D.; Hsu, C. W.; Reid, M. T. H.; Qiu, W.; DeLacy, B. G.; Joannopoulos, J. D.; Soljačić, M.; Johnson, S. G. *Phys. Rev. Lett.* **2014**, *112*, 123903.

- (25) Miller, O. D.; Polimeridis, A. G.; Reid, M. T. H.; Hsu, C. W.; DeLacy, B. G.; Joannopoulos, J. D.; Soljačić, M.; Johnson, S. G. *Opt. Express* **2016**, *24*, 3329–3364.
- (26) Anger, P.; Bharadwaj, P.; Novotny, L. Phys. Rev. Lett. 2006, 96, 113002.
- (27) Kühn, S.; Håkanson, U.; Rogobete, L.; Sandoghdar, V. *Phys. Rev. Lett.* **2006**, *97*, 017402.
- (28) Russell, K. J.; Liu, T.-L.; Cui, S.; Hu, E. L. Nat. Photonics 2012, 6, 459–462.

(29) Rose, A.; Hoang, T. B.; McGuire, F.; Mock, J. J.; Ciracì, C.; Smith, D. R.; Mikkelsen, M. H. *Nano Lett.* **2014**, *14*, 4797–4802.

(31) Eggleston, M. S.; Messer, K.; Zhang, L.; Yablonovitch, E.; Wu,

M. C. Proc. Natl. Acad. Sci. U. S. A. 2015, 112, 1704-1709.

(32) Pelton, M. Nat. Photonics 2015, 9, 427-435.

(33) Purcell, E. M.; Torrey, H. C.; Pound, R. V. Phys. Rev. 1946, 69, 37.

(34) Vesseur, E. J. R.; de Abajo, F. J. G.; Polman, A. Phys. Rev. B: Condens. Matter Mater. Phys. 2010, 82, 165419.

(35) Bohren, C. F.; Huffman, D. R. Absorption and scattering of light by small particles; John Wiley & Sons: Chichester, U. K., 2008.

(36) Faggiani, R.; Yang, J.; Lalanne, P. ACS Photonics 2015, 2, 1739–1744.

⁽³⁰⁾ Akselrod, G. M.; Argyropoulos, C.; Hoang, T. B.; Ciracì, C.; Fang, C.; Huang, J.; Smith, D. R.; Mikkelsen, M. H. *Nat. Photonics* **2014**, *8*, 835–840.

- (37) Novotny, L.; Hecht, B. *Principles of nano-optics*; Cambridge University Press: New York, 2012.
- (38) Esteban, R.; Teperik, T.; Greffet, J.-J. Phys. Rev. Lett. 2010, 104, 026802.
- (39) Moreau, A.; Ciraci, C.; Mock, J. J.; Hill, R. T.; Wang, Q.; Wiley, B. J.; Chilkoti, A.; Smith, D. R. *Nature* **2012**, *492*, 86–89.
- (40) Belacel, C.; Habert, B.; Bigourdan, F.; Marquier, F.; Hugonin, J.-P.; de Vasconcellos, S. M.; Lafosse, X.; Coolen, L.; Schwob, C.; Javaux, C.; Dubertret, B.; Greffet, J.-J.; Senellart, P.; Maitre, A. *Nano Lett.*
- **2013**, *13*, 1516–1521.
- (41) Koenderink, A. F. Nano Lett. 2009, 9, 4228-4233.
- (42) Gonzalez-Tudela, A.; Martin-Cano, D.; Moreno, E.; Martin-Moreno, L.; Tejedor, C.; Garcia-Vidal, F. J. *Phys. Rev. Lett.* **2011**, *106*, 020501.
- (43) Gan, C. H.; Hugonin, J.-P.; Lalanne, P. Phys. Rev. X 2012, 2, 021008.
- (44) Kumar, S.; Kristiansen, N. I.; Huck, A.; Andersen, U. L. Nano Lett. 2014, 14, 663–669.
- (45) Newton, R. G. Scattering theory of waves and particles; Springer: New York, 2013.
- (46) Hamam, R. E.; Karalis, A.; Joannopoulos, J. D.; Soljačić, M. Phys. Rev. A: At., Mol., Opt. Phys. 2007, 75, 053801.
- (47) Ruan, Z.; Fan, S. Phys. Rev. A: At., Mol., Opt. Phys. 2012, 85, 043828.
- (48) Mary, A.; Dereux, A.; Ferrell, T. L. Phys. Rev. B: Condens. Matter Mater. Phys. 2005, 72, 155426.
- (49) Dutta, C. M.; Ali, T. A.; Brandl, D. W.; Park, T.-H.; Nordlander, P. J. Chem. Phys. 2008, 129, 084706.
- (50) Teperik, T.; Degiron, A. Phys. Rev. B: Condens. Matter Mater. Phys. 2011, 83, 245408.
- (51) Rakovich, A.; Albella, P.; Maier, S. A. ACS Nano 2015, 9, 2648–2658.
- (52) Palik, E. D. *Handbook of optical constants of solids;* Academic Press: Waltham, MA, 1998; Vol. 3.
- (53) Kim, S. Appl. Opt. 1996, 35, 6703-6707.
- (54) Yamamoto, N.; Ohtani, S.; Garcia de Abajo, F. J. *Nano Lett.* 2011, 11, 91–95.
- (55) Ruppin, R. Phys. Lett. A 2002, 299, 309-312.
- (56) Hsu, C. W.; DeLacy, B. G.; Johnson, S. G.; Joannopoulos, J. D.; Soljačić, M. Nano Lett. **2014**, 14, 2783–2788.
- (57) Pors, A.; Bozhevolnyi, S. I. ACS Photonics 2015, 2, 228-236.
- (58) Lian, H.; Gu, Y.; Ren, J.; Zhang, F.; Wang, L.; Gong, Q. Phys. Rev. Lett. 2015, 114, 193002.
- (59) Bozhevolnyi, S. I.; Søndergaard, T. Opt. Express 2007, 15, 10869–10877.
- (60) Miyazaki, H. T.; Kurokawa, Y. Phys. Rev. Lett. 2006, 96, 097401.
- (61) Yang, J.; Sauvan, C.; Jouanin, A.; Collin, S.; Pelouard, J.-L.; Lalanne, P. Opt. Express **2012**, 20, 16880–16891.
- (62) Johnson, S. G.; Bienstman, P.; Skorobogatiy, M.; Ibanescu, M.; Lidorikis, E.; Joannopoulos, J. Phys. Rev. E: Stat. Phys., Plasmas, Fluids, Relat. Interdiscip. Top. **2002**, 66, 066608.
- (63) Fernández-Domínguez, A.; Maier, S.; Pendry, J. Phys. Rev. Lett. 2010, 105, 266807.
- (64) Palamaru, M.; Lalanne, P. Appl. Phys. Lett. 2001, 78, 1466–1468.
- (65) Mortensen, N. A.; Raza, S.; Wubs, M.; Søndergaard, T.; Bozhevolnyi, S. I. *Nat. Commun.* **2014**, *5*, 3809.
- (66) Ciraci, C.; Hill, R.; Mock, J.; Urzhumov, Y.; Fernández-Domínguez, A.; Maier, S.; Pendry, J.; Chilkoti, A.; Smith, D. Science **2012**, 337, 1072–1074.
- (67) Yan, W.; Wubs, M.; Mortensen, N. A. Effects of nonlocal response on the density of states of hyperbolic metamaterials. *Proc.* SPIE **2012**, 84550V–84550V.
- (68) Wang, H.; Wu, Y.; Lassiter, B.; Nehl, C. L.; Hafner, J. H.; Nordlander, P.; Halas, N. J. Proc. Natl. Acad. Sci. U. S. A. 2006, 103, 10856–10860.
- (69) Mukherjee, S.; Sobhani, H.; Lassiter, J. B.; Bardhan, R.; Nordlander, P.; Halas, N. J. Nano Lett. **2010**, *10*, 2694–2701.